

UNDERBODY PROTECTION

BLACK

Features:

- Not overpaintable
- Corrosion resistance in salt spray mist according to DIN 50021: 500 hours without rust infiltration at 2 mm film thickness
- High elasticity
- Mandrel test up to 32 mm without fissuring
- Yield: 1,5 m²
- Dry to handle after 3-4 hours
- Dried through after 24 hours
- Temperature resistance from -25 °C to max. 80 °C
- With an anti-humming effect
- Based on Bitumen

Areas of application:

Cartechnic underbody protection is mainly used in the area of underbodies and wheel arches of motor vehicles (cars, caravans, fuel tanks, boats, trucks, spoilers, sills). A thick, elastic layer protects the vehicle against mechanical and chemical stresses such as stone chips, road salt, water, etc., and thus prevents corrosion in particular.

Usage:

Shake well before use. Remove dirt, grease and rust before use. Apply with a sturdy brush. Any soiling of the application equipment can be cleaned with benzine or turpentine substitute in a fresh state. The recommended application thickness is 500 to 600 µm. Optimum processing at 15 °C to 25 °C.

Storage:

Do not store at a temperature below 10 °C and above 30 °C. Protect from exposure to direct sunlight and heat. Store cool.

| Container | Article number: |
|-----------|------------------|
| 500 ml | 40 27289 00427 3 |

Important notice - non-compliance may lead to damage!

Our products are intended for the specified areas of application. If the user wishes to use our products for other purposes, he must check whether the product is suitable and approved for that use. We can only provide a guarantee for the stated specifications. Specifications are subject to change. When we disclose certain examples of use for our products, these may have been carried out in controlled environmental conditions - therefore the results may be different in a different, individual environment. Contact us if you have any questions about the products and application examples! When using, storing and disposing of products, the legal and official regulations, our specifications and the manufacturers' specifications must always be strictly observed. Read the instructions for use, operation and maintenance particularly carefully. Danger warnings must be strictly followed. If the products are handed over to third parties, they must be informed accordingly and the documents belonging to the product, such as manuals, data sheets and hazard warnings, must be made available to them.