## **Product Description**

08/2022



## **MULTI-PURPOSE GREASE**

Lithium saponified, 400g cartridge

## Features:

- Lithium soap grease
- · Walk stable
- Oxidation stability
- Temperature range -30 °C to +120 °C
- Dropping point of + 180 °C
- NL Gl class 2
- Mineral oil base
- Acid-free
- Silicone-free

Area	of	app	olic	atio	n:
		-			

Cartechnic multi-purpose grease lithium saponified can be used for sliding and roller bearing lubrication under normal load.

For general lubrication as well as for demanding lubrication points.

Container	Article number:
400g	40 27289 00134 0

Auto-Teile-Ring GmbH - Marie-Curie-Str. 3 – D-73770 Denkendorf - Tel: +49 (0)711 918979-99 <a href="www.cartechnic.de">www.cartechnic.de</a> - <a href="mailto:info@cartechnic.de">info@cartechnic.de</a>

## Important notice - non-compliance may lead to damage!

Our products are intended for the specified areas of application. If the user wishes to use our products for other purposes, he must check whether the product is suitable and approved for that use. We can only provide a guarantee for the stated specifications. Specifications are subject to change. When we disclose certain examples of use for our products, these may have been carried out in controlled environmental conditions - therefore the results may be different in a different, individual environment. Contact us if you have any questions about the products and application examples! When using, storing and disposing of products, the legal and official regulations, our specifications and the manufacturers' specifications must always be strictly observed. Read the instructions for use, operation and maintenance particularly carefully. Danger warnings must be strictly followed. If the products are handed over to third parties, they must be informed accordingly and the documents belonging to the product, such as manuals, data sheets and hazard warnings, must be made available to them.